

RECTIFIER DIODES MODULE

ADD105

Repetitive voltage up to **2200 V**
Mean forward current **102 A**
Surge current **2,4 kA**

FINAL SPECIFICATION

Jan. 19 - Issue: 0



Symbol	Characteristic	Conditions	T _j [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		150	2200	V
V _{RSM}	Non-repetitive peak reverse voltage		150	2300	V
I _{RRM}	Repetitive peak reverse current	V=VRRM	150	25	mA
CONDUCTING					
I _{F(AV)}	Mean forward current	180° sin, 50 Hz, T _c =100°C, single side cooled		102	A
I _{F(AV)}	Mean forward current	180° sin, 50 Hz, T _c =85°C, single side cooled		123	A
I _{FSM}	Surge forward current	Sine wave, 10 ms without reverse voltage	150	2,4	kA
I ² t	I ² t			29 x 10 ³	A ² s
V _{FM}	Forward voltage	Forward current = 300 A	150	1,53	V
V _{F(TO)}	Threshold voltage		150	0,82	V
r _F	Forward slope resistance		150	2,000	mohm
SWITCHING					
t _{rr}	Reverse recovery time		150		μs
Q _{rr}	Reverse recovery charge				μC
I _{rr}	Peak reverse recovery current				A
MOUNTING					
R _{th(j-c)}	Thermal impedance, DC	Junction to case per element		370,0	°C/kW
R _{th(c-h)}	Thermal impedance	Case to heatsink per element		100,0	°C/kW
T _j	Operating junction temperature			-40 / 150	°C
V _{ins}	RMS insulation voltage	50Hz, circuit to base,all terminal shorted	25	2500	V
T	Mounting torque	Case to heatsink		4 to 6	Nm
		Busbars to terminals		12 to 18	Nm
	Mass			160	g

ORDERING INFORMATION : ADD105 S 22

standard specification VRRM/100



DISSIPATION CHARACTERISTICS

SQUARE WAVE




DISSIPATION CHARACTERISTICS


SINE WAVE






ON-STATE CHARACTERISTIC
T_j = 150 °C



SURGE CHARACTERISTIC
T_j = 150 °C



TRANSIENT THERMAL IMPEDANCE



All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness < .03 mm and roughness < 2 μm.
In the interest of product improvement POSEICO SpA reserves the right to change any data given in this data sheet at any time without previous notice.
If not stated otherwise the maximum value of ratings (symbols over shaded background) and characteristics is reported.

Distributed by

