

FAST RECOVERY DIODE

ARF912

Repetitive voltage up to

2600 V

Mean forward current

754 A

Surge current


6 kA
FINAL SPECIFICATION

June 17 - Issue: 5


Symbol	Characteristic	Conditions	T _j [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		150	2600	V
V _{RSM}	Non-repetitive peak reverse voltage		150	2700	V
I _{RRM}	Repetitive peak reverse current	V=VRRM	150	50	mA
CONDUCTING					
I _{F(AV)}	Mean forward current	180° sin, 50 Hz, Th=55°C, double side cooled		754	A
I _{F(AV)}	Mean forward current	180°square, 50 Hz, Th=55°C, double side cooled		755	A
I _{FSM}	Surge forward current	Sine wave, 10 ms	150	6,4	kA
I ² t	I ² t	riappled reverse voltage up to 50% VRSM		205 x 10 ³	A ² s
V _{FM}	Forward voltage	Forward current = 1200 A	25	2,30	V
V _{F(TO)}	Threshold voltage		150	1,15	V
r _F	Forward slope resistance		150	0,685	mohm
SWITCHING					
t _{rr}	Reverse recovery time	IF= 350A	150	4	μs
Q _{rr}	Reverse recovery charge	di/dt= 80 A/μs		260	μC
I _{rr}	Peak reverse recovery current	VR= 100V		140	A
s	Softness (s-factor), min			0,4	
V _{FR}	Peak forward recovery	di/dt = 400 A/μs	150	20	V
MOUNTING					
R _{th(j-h)}	Thermal impedance, DC	Junction to heatsink, double side cooled		52,0	°C/kW
R _{th(c-h)}	Thermal impedance	Case to heatsink, double side cooled		10,0	°C/kW
T _j	Operating junction temperature			-30 / 150	°C
F	Mounting force			8.4 / 9.4	kN
	Mass			280	g
ORDERING INFORMATION : ARF912 S 26 standard specification <input type="checkbox"/> <input type="checkbox"/> VRRM/100					

DISSIPATION CHARACTERISTICS

SQUARE WAVE (50Hz)



SINE WAVE (50Hz)





ARF912 FAST RECOVERY DIODE




FINAL SPECIFICATION June 17 - Issue: 5


FORWARD RECOVERY VOLTAGE



REVERSE RECOVERY CHARGE Tj = 150 °C




REVERSE RECOVERY CURRENT Tj = 150 °C



$$t_a = I_{rr} / (di/dt) \quad t_b = t_{rr} - t_a$$

$$\text{Softness (s factor)} \quad s = t_b / t_a$$

$$\text{Energy dissipation during recovery } E_r = V_r \cdot (Q_{rr} - I_{rr} \cdot t_a / 2)$$




ARF912 FAST RECOVERY DIODE




FINAL SPECIFICATION June 17 - Issue: 5



FORWARD CHARACTERISTIC
T_j = 150 °C



SURGE CHARACTERISTIC
T_j = 150 °C



TRANSIENT THERMAL IMPEDANCE
DOUBLE SIDE COOLED



Dimensions
in mm



Distributed by

All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness < .03 mm and roughness < 2 μm. In the interest of product improvement POSEICO SpA reserves the right to change any data given in this data sheet at any time without previous notice. If not stated otherwise the maximum value of ratings (symbols over shaded background) and characteristics is reported.

